

SafetyTech®

SPECIAL DUTY



Designed for spider-type lifts, portable tracked aerial equipment and mini cranes.

SLIDING SHOE
Let us design a custom solution for you!



SMART

Pads easily fit onto stabilizer feet and lock in place. Equipment can be re-positioned or secured for travel without having to stow outrigger pads.

+



SLIDES EASILY

Pads allow stabilizer feet to slide safely and securely within the pad. This provides less re-positioning of the equipment and reduced downtime for crews.

+



SIMPLE

Unlocking the pad to insert the foot couldn't be easier. Simply unscrew the stop block knob, insert the foot, replace the stop block and secure the knob.

=



SAFE

Sliding shoe outrigger pads by DICA deliver a simple, safe and efficient stabilizer pad setup you can always trust. Crew fatigue is also minimized.

MODEL	W X L X H (in)	FOOT OPENING (in)	WEIGHT (lbs)	PAD THICKNESS (in)	SIDEWALL HEIGHT (in)	CRUSH RATING (psi)	WORKING LOAD LIMIT (lbs)	MAXIMUM RATED CAPACITY (lbs)
DS922-3	9.25" X 22" X 3"	7.5"W X 1"H	12	1.0"	1.0"	200	18,000	100,000
DS1124-3	11" X 24" X 3"	8.375"W X 1"H	13	1.0"	1.0"	200	18,000	100,000
DS1124-3.5	11" X 24" X 3.5"	8.375"W X 1"H	17	1.5"	1.0"	300	20,000	125,000
DS1224-3.5	12" X 24" X 3.5"	9.75"W X 1.5"H	14	1.0"	1.5"	200	18,000	100,000

Custom sizes available. Foot specifications required.

