

“Every crane in my fleet is equipped with a set of DICA Pads, and always will.”

Ross Kovach

ROSSCO CRANE & RIGGING



PRODUCT DETAILS

- Engineered Thermoplastic Material
- TuffGrip® Handles
- Waterproof and Chemical Resistant
- Industrial Grade Safety Texturing
- Radius Edges and Corners
- Non-Conductive
- 1-2 Person Carry or Roll
- Guaranteed Unbreakable

BEST FOR

- Mobile Cranes
- Concrete Pumpers
- Aerial Lifts
- Digger Derricks

PRODUCT	W x L x H (in)	THICKNESS (in)	APPROX AREA (sq ft)	WEIGHT (lbs)	CRUSH RATING* (psi)	WORKING LOAD LIMIT* (lbs)						
2" Pads												
A D1515-2	15 x 15 x 2	2 inch	1.5	15	500	65,000						
B D1818-2	18 x 18 x 2	2 inch	2	20	500	70,000						
C D2424-2	24 x 24 x 2	2 inch	4	38	500	80,000						
D D2424-2-Y	24 x 24 x 2	2 inch	4	38	500	80,000						
E D2424-2-O	24 x 24 x 2	2 inch	4	38	500	80,000						
F D3030-2	30 x 30 x 2	2 inch	6	60	500	95,000						
G D3636-2	36 x 36 x 2	2 inch	9	86	500	110,000						
H D4242-2	42 x 42 x 2	2 inch	12	120	500	125,000						
I D4848-2	48 x 48 x 2	2 inch	16	150	500	140,000						
J DR30-2 (Round)	30 x 2	2 inch	5	45	500	85,000						
K DR36-2 (Round)	36 x 2	2 inch	7	68	500	100,000						
L DR42-2 (Round)	42 x 2	2 inch	9.5	92	500	115,000						
M DR48-2 (Round)	48 x 2	2 inch	12.5	120	500 </tr <tr> <td>N DR60-2 (Round)</td> <td>60 x 2</td> <td>2 inch</td> <td>19.5</td> <td>190</td> <td>500</td> <td>160,000</td> </tr>	N DR60-2 (Round)	60 x 2	2 inch	19.5	190	500	160,000
N DR60-2 (Round)	60 x 2	2 inch	19.5	190	500	160,000						



Crush Rating – The maximum allowable pressure. **Working Load Limit** – The maximum allowable load based on the application.

