



ProStack Slot Lock Cribbing



Safely Add Height in Minutes!



100% Recycled

ProStack Cribbing is made from a combination of post-consumer recycled material and additives to produce a strong, reliable, and environmentally friendly solution. All ProStack cribbing products are warranted for 25 years against rot, insect infestation, splitting, cracking or splintering.

Strong

Unlike most cribbing solutions commonly deployed in the field, ProStack's engineered material is extremely strong and impervious to weather and jobsite conditions. The setup of a SafetyTech Base Pad and two ProStack Blocks has a 100,000 lbs working load limit and a max allowable pressure of 500 psi.

Interlocking Design

ProStack Slot Lock flanges interlock with a DICA SafetyTech® base pad and with additional block layers when positioned in alternating directions. Each layer increases cribbing height by five inches, and the surface allows room for outrigger feet measuring up to 18"x18."

Lightweight

Each block weighs less than 30 lbs, which minimizes operator fatigue and provides quick setup and breakdown times. Molded grips make it easy for one person to carry and position blocks, even when wearing gloves. TuffGrip® handles can be added as an option to facilitate carrying two blocks at once.

MODEL	SLOT LOCK	DIMENSIONS (in)	APPROX AREA (sq ft)	WEIGHT (lbs)	MAX ALLOWABLE PRESSURE (psi)	WORKING LOAD LIMIT (lbs)
SafetyTech Outrigger Pads						
A PSC-SL-D2424-1.5	Yes	24 X 24 X 1.5	4	29	500	100,000*
B PSC-SL-D2424-1.5-Y	Yes	24 X 24 X 1.5	4	29	500	100,000*
Cribbing Block						
C PSC-SL-100	Yes	21.5 X 9 X 6	1	28	500	100,000*
Neoprene Grip Pad (Optional feature to increase friction between your outrigger foot and the cribbing blocks)						
D NP1818.75	N/A	18 X 18 X 0.75	2	4	N/A	N/A

* Working Load Limit and Max Allowable Pressure ratings are based on a minimum slot lock setup of one SafetyTech Base Pad & two ProStack Slot Lock Cribbing Blocks.

