



SafetyTech Steel Dunnage



DICA's multi-pad configuration utilizes the unique properties of steel and DICA's engineered thermoplastic. The patent-pending modular system is specifically designed for the daily challenges concrete pump operators face and can be deployed by a single person to reduce the ground bearing pressure.

SafetyTech Steel Dunnage uses the lightest weight steel and the lowest cost parts that when combined, creates a unified solution that is repeatable, long lasting and efficient.

BM-0080

KEY FEATURES

- ▶ Lightweight solution is packed into a one-person modular system that incorporates the best of steel and plastic.
- ▶ Ground bearing pressures are reduced and the entire pad configuration is engaged when working on soil.
- ▶ Materials will never rot, warp, splinter, delaminate, deteriorate or waterlog.
- ▶ Easy to clean and is resistant to water, chemicals, bacteria and other contaminants.
- ▶ Engineered and manufactured in the USA.



DUNST-60-13-18 Dunnage Kit

Total Area: 13.5 sq. ft
 Total Capacity: 60,000 lbs
 Total Parts: 8
 Total Weight: 322 lbs
 Max Outrigger Float: 18"

DUNST-110-18-18 Dunnage Kit

Total Area: 18 sq. ft
 Total Capacity: 110,000 lbs
 Total Parts: 8
 Total Weight: 500 lbs
 Max Outrigger Float: 18"

COMPONENTS	WxLxH (in)	WEIGHT (lbs)
Base Pads (3)	18 X 36 X 2	40
Steel Tubes (4)	4 X 6 X 32	31
Top Pad (1)	24 X 24 X 2	78
Base Pads (3)	21 X 42 X 3	90
Steel Tubes (4)	4 X 6 X 36	34
Top Pad (1)	24 X 24 X 2	94

