



ProStack Pyramid Lock Cribbing Blocks



Get the height you need without compromising safety or stability using ProStack Pyramid Lock Cribbing Blocks. This is a heavy duty solution ideal for supporting cranes with loads up to 110,000 pounds and a 24"x24" outrigger float.

DICA's ProStack Pyramid Lock Blocks combine variable height with interlocking stackability that gives operators the ability to safely crib up.

KEY FEATURES

- ▶ Stacking height is 6" per block.
- ▶ Contact surface is 24"x24" when two blocks are placed side by side.
- ▶ TuffGrip Handles allow for easier pick up, deployment and retrieval.
- ▶ Made from material that will not splinter, crack, rot or delaminate.
- ▶ 4-step setup and teardown process.



ProStack Pyramid Lock Setup

4 STEPS TO A SAFE SETUP



Step 1

The base SafetyTech Outrigger Pad is positioned first with the Pyramid-shaped surface facing upward to receive the interlocking pyramids on the cribbing blocks.



Step 2

The first layer of (2) ProStack cribbing blocks are added. Pyramid shapes interlock into the base pad.



Step 3

The second layer (2) of ProStack cribbing blocks are added, perpendicular to the bottom layer.



Optional Step 4

A Neoprene Friction and Ground Softening pad can be placed on top of the stack to provide a high friction surface for the outrigger foot and protect the pyramid surface on the blocks.

	MODEL	INTERLOCKING PYRAMIDS	DIMENSIONS (in)	APPROX AREA (sq ft)	WEIGHT (lbs)	CRUSH RATING (psi)	WORKING LOAD LIMIT (lbs)
Outrigger Pads with Interlocking Pyramids	PSC-D2424-2	YES	24 X 24 X 2	4	38	500	80,000
	PSC-DR36-2	YES	36 X 2	7	68	500	100,000
	PSC-DR42-2	YES	42 X 2	9.5	92	500	115,000
	PSC-DR48-2	YES	48 X 2	12.5	120	500	130,000
Cribbing Blocks with Interlocking Pyramids	PSC-1212-6	YES	12 X 12 X 6	1	26	500	55,000
	PSC-2412-6	YES	24 X 12 X 6	2	55	500	110,000
Neoprene Grip Pads High-Friction Grip Pad (Optional)	G NP-1212-.75	N/A	12 X 12 X 0.75	1	4	N/A	N/A
	H NP2424-.75	N/A	24 X 24 X 0.75	4	16	N/A	N/A

