



LevelRight Outrigger Pads



Creating a level surface for your equipment's outriggers does not have to be difficult or time-consuming. With DICA's LevelRight pads, you can establish a level surface quickly, saving time and effort on every setup.

Ideal for operators of cranes, concrete pumps, jacking applications, and other equipment with outriggers, LevelRight's engineered wedges rotate to establish a level foundation on uneven surfaces. Operators can simply place LevelRight on supporting materials, adjust the product until the built-in bubble level confirms it is level, and get to work.

KEY FEATURES

- ▶ Innovative product saves time and improves safety by eliminating the need for wedges or scrap wood.
- ▶ Enables operators to address unlevel surfaces in multiple planes; adjustable from 0-10 degrees.
- ▶ Rated capacity of 350,000 lbs.
- ▶ Accepts up to 20" square and 24" circular outrigger floats.
- ▶ Built-in bubble level makes it easy to confirm level surface.
- ▶ Made from our proprietary engineered thermoplastic material that's impervious to water, resistant to chemicals, and guaranteed to be unbreakable.



MODEL	DxH (in)	AREA (sq ft)	WEIGHT (lbs)	RATED CAPACITY (lbs)	MAXIMUM ALLOWABLE PRESSURE (psi)
LRST-24	24 x 3.25	3	50	350,000	1000

